

# QUATRO

## 3000 AND 4500

MULTI-  
PROCESS

2 YEAR  
WARRANTY

100% DUTY  
CYCLE @ 40°C

MICRO-  
PROCESSOR



# W

**WOLFRAM**

MINING SUPPLIES

sales@wolfram.co.za

www.wolfram.co.za

# STAR WELD

**WELDING  
PRODUCTS**

MADE IN  
SOUTH AFRICA



The Starweld range of multi-process, inverter based welding machines, are microprocessor controlled. These microprocessors reduce the component count, provide greater output consistency, and are capable of memorizing, multiple welding parameters simultaneously.

### FEATURES

- ★ **Versatile Multi-process Capability** - Including Stick, Lift TIG DC, MIG, flux-cored welding and carbon arc gouging up to a 9.5mm carbon.
- ★ **High Duty Cycle** - Designed to deliver 100% duty cycle at maximum current with ambient temperatures up to 40°C.
- ★ **TIG Arc Control Menu** - An easy start Lift/Tig arc initiation. The start / finish current, the up and down slopes, the pre and post gas flows, can all be adjusted. There is also a pulsing feature, for welding of thin materials.
- ★ **Manual Metal Arc Control Menu** - When performing manual metal arc welding, the arc can be adjusted to obtain a softer or more aggressive arc characteristic.
- ★ **MIG Arc Control Menu** - The rate of current rise and fall in the MIG mode can be controlled to reduce spatter, improve fluidity, and to enhance bead appearance.
- ★ **Digital Amp and Volt Meters** - Bright display of welding parameters, both presetable and actual.
- ★ **Unique Cooling System** - The "tunnel" cooling design, protects critical components and printed circuit boards free from dust.
- ★ **Robust Construction** - Components are securely mounted to enable the machine to operate in hazardous environments, including being mounted on generator sets.
- ★ **Two Year Warranty** - Warranty on all parts and labour.

### AVAILABLE OPTIONS

Wire Feeder



Water Cooler



Undercarriage



Remote Control



Foot Pedal



Volt Loc  
VRD



Welding Safety



Technical Specifications	Quatro 300	Quatro 450
Input Voltage	360V - 575V	360V - 575V
Input Current	22.7A - 14.2A	40.4A - 25.3A
Rated Output Voltage	32V	38V
Rated Output Current	300A	450A
Duty Cycle @ 40°C Ambient	100%	100%
Dimension - W x H x L mm	350x370x620	350x370x620
Weight	31kg	31kg