

4WD

24VAC / OTHER



The Starweld range of 4WD wire feeders are micro processor controlled, offering a full variable, smooth, wire feed selection. In addition the feeder is fitted with both voltage and amperage controls, as well as a trigger lock function.

FEATURES

- Remote Voltage Control power source voltage remotely from wire feeder.
- Water Cooled Option On water cooled equipment, water quick couplers provided for torch inlet and outlet water flow.
- Dual Voltage Option Wire feeder available with an 110VAC and 24VAC supply input in order to operate off other brands of equipment.
- Long Base Option A longer wire feeder base is also available designed to carry a 27kg wire spool. Standard version has the capacity to carry a 15kg wire spool.
- **4WD Motor** Powerful 4 wheel drive motor suitable for wire diameters from 0.6mm to 3.2mm.
- Roller Options V, U and Knurled rollers available for different wire types.
- Ramp Up / Burnback Internally adjustable.
- **2T / 4T -** 2 Step and 4 Step trigger selected via mode button.
- Robust Construction Components are securely mounted to enable the machine to operate in hazardous environments, including being mounted on generator sets.
- Two Year Warranty Warranty on all parts and labour.



ST R WELDING PRODUCTS	1		
	Input Current	3.5A	
	Rated Output Voltage		
	Rated Output Current	500A	
	Duty Cycle @ 40°C Ambient	60%	
	Dimension - W x H x L mm	280x360x590	
	Spool Capacity	15kg - Std	27kg - LB

Input Voltage

Technical Specifications

